

Strip Door Curtain System

Fast-Mount Strip Door

Applications

Retail
Supermarket
Distribution Centers
Warehouses
Manufacturing
Restaurants
Cold Storage Facilities

Environment

Freezer
Cooler
Personnel
Interior
Exterior
Loading Dock
Washdown

Traffic

Personnel
Cart
Pallet Jack
Light Forklift Traffic

Options

Standard Clear
USDA Low Temp
Loc-Rib
Low Temp Reinforced

Chase Doors makes the job of hanging strip doors even easier with our new Fast-Mount strip door system. The Fast-Mount design eliminates multiple studs and fasteners, and ensures a simple, fast installation. A 3' x 7' strip door can be installed in a matter of minutes. Simply attach the mounting bracket to the wall, slide the J-Hook Strips into the bracket and install the locking screws at each end to hold the strips in place. No more time consuming layout, measuring or calculating overlap of strips. Fast-Mount strips are designed so that they install and establish a preset overlap when you slide them into the bracket.



Mounting Brackets

Low profile aluminum extrusion is inherently strong and maintains a minimum clearance from the wall. J-Hook strips slide easily into the bracket for installation, and can be replaced when necessary in little or no time.

J-Hook Sliding Hanger and Strip Material

The J-Hooks have a continuous welded bond between each strip. 6" and 8" strip material has a standard 2" overlap on each side. The strips are tapered, making installation fast and easy. If the strips ever come unsealed from the J-Hook we guarantee free replacement including freight.

Hangs Flat Right Out of the Box

No need to lay strips out for 24 hours prior to installation. When you are ready to install, just open, hang and you are done!

Installation is Easy as 1, 2, 3!



Attach the mounting bracket to a flat surface above the opening.



Start at either end & slide the J-Hook Hanger/Strips along the center track in the Fast-Mount bracket until all strips are installed.



Install a locking screw in each end of the bracket to hold the strips in place and you are done – fast and easy!



J-Hook
Hanger

Fast-Mount Strip Door

Product Details - Specifications, Door Sizes & Material Options

Part 1 - General

1.1 Section Includes - PVC Strip Door and Curtain Systems.

Part 2 - Products

2.1 Manufacturer - PVC Strip Door and Curtain System to be model Fast-Mount Strip Door by Chase Industries, Inc. (DBA Chase Doors).

2.2 Door Components - Strip material shall be 6" or 8" wide. 6" wide shall be 6" x .060 thick with a 67% overlap(6602). 8" wide shall be 8" x .080" thick with 50% overlap (8802). Material choice shall be Standard Clear, Loc-Rib, USDA Low Temp and Low Temp Reinforced. Loc-Rib only available in 8" x .080". Strips shall have a continuous welded bond to the J-Hook hanger. Strips to overlap 2" per side and shall be flush with the end of the bracket. The Fast-Mount Strip Door is available in the following sizes:

Model 6602 (6" x .060 thick with a 67% overlap)
Widths – 26", 30", 34", 38", 42", 46", 50", 54", 58", 62", 66", 70", 74", 78", 82", 86", 90", 94", 98"
Maximum Height – 120"

Model 8802 (8" x .080" thick with 50% overlap)
Widths – 26", 32", 38", 44", 50", 56", 62", 68", 74", 80", 86", 92", 98", 104", 110", 116", 122"
Maximum Height – 120"

2.3 Mounting Hardware - Mounting bracket is a one piece extruded aluminum bracket for face of wall mounting only. Center track accommodates J-Hook hangers.

2.4 Fabrication - Provide strip door assemblies manufactured as integral units ready for assembly and installation. Mounting Bracket: for metal surface exposed to view in completed work, provide materials with smooth flat surface without blemishes. Do not use materials with exposed pitting, seam marks, roller marks, rolled trade names or roughness. PVC Strip Curtain: provide PVC Strip cut to size, of clear materials without blemishes, scratches or irregularities. Material thickness to be not more than .008 under specified thickness, and more than 1/8" under in standard material width.

Part 3 - Execution

3.1 Installation - Install doors in accordance with Chase Industries instructions and standards.

Material Options

Standard - Our clear PVC strips are designed for use in most walk-in coolers or in doorways at ambient temperatures with personnel, cart, pallet jack and light forklift traffic.

USDA Low Temp - Clear PVC formulated to remain pliable in food service freezer temperatures; also for use in areas where USDA accepted material is required.

Loc-Rib™ - Our standard and USDA grade PVC strips can be fabricated with "locking" ribs to seal against air flow in cooler or freezer temperatures. Ribs also preserve strip clarity by absorbing abrasions. Not available in 6" x .060".

Low Temp Reinforced - Nylon reinforced strips remain pliable in freezers subjected to heavy personnel, hand truck or fork lift traffic.



Mounting Bracket



World's Leading Manufacturer of Specialty Doors

Chase Industries, Inc.

Cincinnati • Redmond

Toll-Free: 800.543.4455 • 513.860.5565 • Fax: 800.245.7045

Web site: www.chasedoors.com • www.coldstoragedoorsonline.com

E-mail: info@chasedoors.com

